मौलाना आज़ाद नेशनल उर्दू यूनिवर्सिटी مولانا آزاد प्रानी है ।

MAULANA AZAD NATIONAL URDU UNIVERSITY



(A Central University)

No. MANUU/ES/F01/2018-19/ 236

Dated £/0920108

NIQ No. MANUU/ES/ 32/2018-19/236 Dated 0909/2018

The Executive Engineer, MANUU, Hyderabad invites on behalf of the Vice-Chancellors, Sealed item rate quotations from CPWD contractors for the following work so as to reach this office up to 15:00 PM on 12/09/2018 and will be opened on the same day at 15:30 hours. Blank quotation forms can be obtained from this office at free of cost up to 14:00 Hours on 12/09/2018.

Name of Work: Removing and relaying of Cement concrete paver blocks foot path in the Central

Lowns at MANIII. Hyderabad.

Item	Description of Item	Quantity	Unit	Rate		
No.				In Fig	In words	Amount
No.		attached Sche			In words	

Terms and Conditions:

- The work shall be carried out as per CPWD Specifications 2009 Volume-I & II with up to date correction slips and as per the specification of the manufacturer.
- 2. The work should be completed within Fifteen (15) days from the date of Issue of the Work Order.
- The rates should be quoted in figures and words and inclusive of all taxes, duties and nothing will be paid extra.
- 4. The contractor has to make his own arrangements for water and power etc., which is required for the completion of the work.
- 5. Necessary recoveries as applicable will be deducted from the bill.
- 6. The payment will be made after satisfactory of completion of work.

CONTRACTOR Address

Executive Engineer

Copy to:

The Registrar, MANUU, Hyderabad.

- The Director, CIT, MANUU, Hyderabad for uploading the NIQ in the University Web site.
- 3. Notice board, MANUU.

Executive Engineer

Schedule of Quantities

me of work: Removing and relaying of Cement concrete paver blocks foot path in the Central Lawns at MANUU,

dei	abad.				ъ.	
No	DESCRIPTION	Qty	Unit	Rate In Fig	Rate In Words	Amount
	Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including disposal of excavated earth upto 50 m and lift upto 1.5 m, disposed soil to be levelled and neatly dressed:					
.1	All kinds of soil	200.00	Sqm			
2	Providing and laying in position ready mixed plain cement concrete, with cement content as per approved design mix and manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for plain cement concrete work, including pumping of R.M.C. from transit mixer to site of laying and curing, excluding the cost of centering, shuttering and finishing, including cost of curing, admixtures in recommended proportions as per IS: 9103 to accelerate/retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer-in-charge. Note: 1) Excess/less cement used than specified in this item is payable/recoverable separately.					
2.1	All works upto plinth level					
.1.1	M-10 grade plain cement concrete (cement content considered @ 220 kg/cum)	20.00	Cum			
3	Removing 60mm thick cement concrete interlocking paver blocks from the existing path, cleaning the sand, deposits etc., complete and stacking as per direction of the Engineer-in-charge.	240.00	Sqm			
4	Removing the existing kerb stone of cement concrete from the existing path, cleaning the concrete deposits etc., complete and stacking as per direction of the Engineer-in-charge.	265.00	metre			

lo	DESCRIPTION	Qty	Unit	Rate In Fig	Rate In Words	Amount
	Refixing and Relaying 60mm thick cement concrete interlocking paver blocks over and including 50mm thick compacted bed of coarse sand, filling the joints with line sand etc. all complete as per the direction of Engineer-in-charge. Note: Old Precast C.C. interlocking paver blocks shall be used after removing and cleaning them from existing path. Labour rate only including the cost of sand bed but excluding the cost of interlocking paver blocks.	195.00	Sqm			
,	Relaying Kerb stones of cement concrete of size 600*450* 125 mm at or near ground level in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-incharge (length of finished kerb edging shall be measured for payment). Note: Old Precast C.C. kerb stone shall be used after removing and cleaning them from existing path. Labour rate only including the cost Cement mortar but excluding the cost of kerb stones.					
		195.00	metre			

Terms and Conditions:

- The work shall be carried out as per CPWD Specifications 2009 Volume-I & II with up to date correction slips and as per the directions of the
- The work should be completed within 15 (fifteen) days from the date of Issue of the Work Order.
- The rates should be quoted in figures and words and inclusive of all taxes, duties and nothing will be paid extra.
- The contractor has to make his own arrangements for water and power etc., which is required for the completion of the work. 4.
- Necessary recoveries as applicable will be deducted from the bill. 5.
- The payment will be made after satisfactory of completion of work and as per actual measurements recorded. 6.

Signature of Contractor Seal & Address

Executive Engineer MANUU

Total